Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-40. (Canceled)
- 41. (Currently Amended) An apparatus for manufacturing a color filter, comprising:

a plurality of nozzles for ejecting a filter material in droplets; and
a plurality of ejection heads which are arranged perpendicular to a head scan
direction arranged on a print head, each ejection head which ejects a different filter material
having the plurality of nozzles linearly arranged with a constant layout pitch of (D), the
plurality of ejection heads are arranged on the print head to form only at least a single linear
row of nozzles, nozzles which is arranged perpendicular to the head scan direction,

wherein a plurality of types of filter material are each concurrently ejected from nozzles in the single linear row of nozzles on the print head.

42. (Currently Amended) An apparatus for manufacturing an electroluminescence substrate, comprising:

a plurality of nozzles for ejecting a filter material in droplets; and
a plurality of ejection heads which are arranged perpendicular to a head scan
direction arranged on a print head, each ejection head which ejects a different filter material
having the plurality of nozzles linearly arranged with a constant layout pitch of (D), the
plurality of ejection heads are arranged on the print head to form only at least a single linear
row of nozzles, nozzles which is arranged perpendicular to the head scan direction,

wherein a plurality of types of filter material are each concurrently ejected from nozzles in the single linear row of nozzles on the print head.

43. (Currently Amended) A method for manufacturing a color filter, comprising:

scanning a substrate by moving a table and a plurality of ejection heads which

are arranged perpendicular to a head scan direction arranged on a print head; and

ejecting a plurality of types of filter material in droplets by the plurality of ejection heads, each ejection head which eject a different filter material having a plurality of nozzles arranged with a constant layout pitch of (D), the plurality of ejection heads being linearly arranged to form only at least a single linear row of nozzles, nozzles which is arranged perpendicular to the scan head direction.

wherein the plurality of types of filter material are each concurrently ejected from nozzles in the single linear row of nozzles on the print head.

44. (Currently Amended) A method for manufacturing an electroluminescence substrate, comprising:

scanning a substrate by moving a table and a plurality of ejection heads which are arranged perpendicular to a head scan direction arranged on a print head; and

ejecting a plurality of types of functional layer forming material in droplets by a plurality of ejection heads, each ejection head which eject a different filter material having a plurality of nozzles arranged with a constant layout pitch of (D), the plurality of ejection heads being linearly arranged to form only at least a single linear row of nozzles, nozzles which is arranged perpendicular to the head scan direction,

wherein a plurality of types of filter material are each concurrently ejected from nozzles in the single linear row of nozzles on the print head.